

Redpost PU-Monitor



Redpost PU-Monitor

General product information

Through pasteurization, the number of micro-organisms in beer and beverages are reduced and consequently their shelf life increased. To maintain the quality of the product with regard to taste, smell, brightness and color, pasteurization should be a gentle heat treatment. The most commonly used method of pasteurization makes use of a tunnel pasteurizer, through which containers, like glass bottles or cans, travel while being sprayed with warm water. The effect of heat treatment in relation to time is expressed in pasteurization units (PUs).

The Redpost PU-Monitor, type RPU-352, monitors the pasteurization process and accurately calculates the pasteurization units. In addition, it measures the spray water temperature in the tunnel pasteurizer.

The container is placed in the PU-Monitor, which travels with all the other containers through the pasteurizer. During the process, the PU-Monitor measures and stores the product temperature inside the container in relation to the time and subsequently calculates the PUs. Moreover, the spray water temperature is measured, to determine the condition of the pasteurizing tunnel and the relation between the spray water temperature and the temperature in the container. After the pasteurizing process is finished, the PUs are displayed immediately on the PU-Monitor. The data can be transferred to a PC or printer by means of Haffmans Charger/Interface, which charges the battery of the PU-Monitor.



RPU-352

Redpost PU-Monitor



Benefits

- Perfect process control
- Cost saving
 - reduction of product loss
 - optimizing energy consumption
 - low maintenance

Applications

- Tunnel pasteurizer

Technical Data

Measuring range

Temperature:	-5 to 105 °C
Pasteurization units:	0 to 9999.9 PU

Accuracy (in range 40 - 80 °C)

Temperature:	< 0.25 °C
Pasteurization units:	< 8 %

Container dimensions:	Height 82 - 400 mm* Outside diameter 45 - 100 mm*
PU calculation factors:	programmable
Measuring:	2 x temperature
Recording interval:	10 s (adjustable from 2 - 60 s)
Storage capacity:	4 recordings, maximum 4 h per recording

Dimensions:	380 x 175 x 230 (LxWxH in mm)
Weight:	8.5 kg

* When ordering, please state which container dimensions the PU-Monitor should be suitable for.

Scope of Supply

- Redpost PU-Monitor, type RPU-352
- Temperature probe (Standard 230 mm)
- Spray water temperature probe
- Bottle holder Ø 55 - 68 mm
- Operating magnets
- Test plug (60 °C)
- Dummy temperature probe
- Key plug
- Connector grease
- Instruction Manual

Options

- Certificate of Measurement
- Can holder
- Charger/Interface RPC-80
- Charger/Interface RPC-50



Haffmans BV

P.O. Box 3150 NL-5902 RD Venlo • The Netherlands

T +31 77 323 23 00 • F +31 77 323 23 23

E info@haffmans.nl • I www.haffmans.nl

Please visit our website to obtain information about your local support.

Haffmans BV reserves the right to make changes in the technical specifications at any time.

RPU-352